

CDM :HAZARD IDENTIFICATION - HANDLING MATERIALS

BE AWARE OF SHARP EDGES AND CORNERS WHEN HANDLING MATERIALS. MOST EDGES AND CORNERS WILL BE DEBURRED BUT THERE IS STILL A SMALL RISK. WEAR APPROPRIATE PPE REQUIRED FOR THE TASK. THE MHOR 1992 SET OUT A CLEAR RANKING OF MEASURES FOR DEALING WITH RISKS FROM MANUAL HANDLING, THESE ARE:

FIRST : AVOID HAZARDOUS MANUAL HANDLING OPERATIONS SO FAR AS IS REASONABLY PRACTICABLE;

SECOND : ASSESS ANY HAZARDOUS MANUAL HANDLING OPERATIONS THAT CANNOT BE AVOIDED; AND

THIRD : REDUCE THE RISK OF INJURY SO FAR AS IS REASONABLY PRACTICABLE.

HAND PROTECTION (MANDATORY) TO: BS EN 388:1994.

ROOFLIGHTS MUST ONLY BE INSTALLED BY COMPETENT CONTRACTORS.

ANGER OF DAMAGING GLASS IF IT IS WALKED UPON. GLASS IS CLASSED AS NON-FRAGILE BUT SHOULD NOT BE WALKED ON. USE SPREADER BOARDS.

REFER TO RISK ASSESSMENT FOR FURTHER DETAILS.

NOTES

X No. REQUIRED

GLASS SPEC:
OUTER : 33mm CLEAR HST TOUGHENED AND LAMINATED GLASS - 10/1.5/10/1.5/10
- PVB OR SGP INTERLAYER + BLACK BORDER ON FACE 2
CAVITY : 20mm ARGON FILLED + WARM EDGE SPACER + DC3363 UV RESISTANT SILICONE BOND
INNER : 6mm CLEAR HST TOUGHENED GLASS OR 13.5mm LAMINATED + LOW E TO CAVITY FACE

LIGHT TRANSMISSION = 73.2%
SOLAR GAIN = 46.8 g
CENTRE PANE U-VALUE = 1.1 W/m².K
ACOUSTIC = NPD
ROOFLIGHT ORDER SIZE = OVERALL FINISHED AND WEATHER KERB DIMS.

GLASS BONDED TO FRAME WITH GLAZING SECURITY TAPE - TN136.

KERB DETAILS SHOWN INDICATIVE DETAILED DESIGN BY OTHERS.DETAILED DESIGN BY OTHERS TO MEET CURRENT BUILDING REGS. AN APPROVED DOCUMENT PART L COMPLIANT FULLY INSULATED TIMBER KERB IS AVAILABLE FROM ROOFGLAZE ROOFLIGHTS LTD.

RECOMMENDED FALL SHOWN TO HELP SHED WATER ONLY. UNIT CAN BE INSTALLED AT LOWER PITCHES. HIGHER IF NO WATER AT ALL IS DESIRED.

PRODUCT U-VALUE = 1.6 W/m².K (SIZE DEPENDENT)
CENTRE PANE U VALUE = AS LOW AS 1.0W/M².K TO SPECIAL ORDER.
WEIGHT = APPROX. 127 KG. (SIZE DEPENDENT)

FLOOR LOADINGS TO BS EN 1991-1-1:

1.5 kN/m² Uniformly distributed load

2.0 kN Concentrated load

4.0 kN/m² Uniformly distributed load

3.6 kN Concentrated load

5.0 kN/m² Uniformly distributed load

4.5 kN Concentrated load

THESE LOADS ARE ARBITRARY. GLASS THICKNESS MAY VARY DEPENDING ON LOADS. LOADS TO BE AGREED/ SPECIFIED BY CLIENT.

PAINTED BORDER SHOWN AS STANDARD TO COVER GLAZING FRAME.

DIMENSIONS SHOWN DOWN THE SLOPE.

DIMENSIONS SHOWN TO TOP OF GLASS ARE APPROXIMATE.

SEALING TO SURROUNDING CONSTRUCTION BY OTHERS.

THE MANUFACTURER RECOMMENDS AN ANTI-SLIP COATING TO WALK ON GLASS. DATA SHEET AVAILABLE FROM:
HTTPS://WWW.ROOFGLAZE.CO.UK/RESOURCES/TECHNICAL-DATA-SHEETS/

WEIGHT FOR A 1m² UNIT:
33/6 GLASS = 113 KG
39/6 GLASS = 128 KG
48/6 GLASS = 150 KG

OVERALL ROOFLIGHT SIZE = OVERALL KERB + 45

CRITICAL DIM = OVERALL KERB LENGTH, INCLUDING ROOF FINISHING

BLACK BORDER WITHIN THE GLASS MAKE UP

RECOMMENDED 5° FALL

PLAN VIEW
True view on slope

CRITICAL DIM = OVERALL KERB SPAN, INCLUDING ROOF FINISHING

OVERALL ROOFLIGHT SIZE = OVERALL KERB + 45

3D EXAMPLE OF KERB

3D RENDER IMAGING OF FRAME

EXPLODED INSTALL GUIDE

OVERALL ROOFLIGHT SIZE = OVERALL KERB + 45

GLASS

STRUCTURED SILICONE JOINT BLACK

DRAINAGE ROUTE

ANY SURROUNDING CONSTRUCTION BY OTHERS

KERB ADAPTOR BEDDED ON EXPANDING TAPE OR BUTYL

KERB FIXING SCREW

ROOF FINISHES BY OTHERS

ANY SURROUNDING CONSTRUCTION & DRAINAGE BY OTHERS

WHITE/ BLACK uPVC FRAME SHIELD (BLACK STANDARD)

GAP DEPENDANT UPON GLASS WEIGHT

COMPLETE SILICONE WEATHER. DC 791 OR SIMILAR BY OTHERS

ROOF FINISH BY OTHERS

ANY TANKING OR WATERPROOFING BY OTHERS

CRITICAL DIMENSION = EXTERNAL WEATHERED KERB

ANY SEALANT TO PERIMETER OF FRAME MUST BE FLEXIBLE TO ALLOW FOR DIFFERENTIAL MOVEMENT

ANY SURROUNDING CONSTRUCTION BY OTHERS

ROOF FINISH ON TOP OF KERB BY OTHERS

SECTION A-A

SECTION B-B

IF IN DOUBT ASK DO NOT SCALE	IT IS THE RESPONSIBILITY OF THE KERB DESIGNER TO ENSURE THE KERB WILL BE STRUCTURALLY ADEQUATE TO HOLD THE ROOFLIGHT. KERBS SHOWN ON THESE DRAWINGS ARE FOR ILLUSTRATION PURPOSES ONLY.	The manufacturer would advise an installation with a minimum pitch of 5° for rooflight units to minimize water pooling. Whilst the product can be installed flat without detriment to the warrantee, the manufacturer cannot be held responsible for any excessive pooling of water to the surface of the rooflight, post installation, if installed without an adequate fall, larger units may require a greater fall. The final decision on amount of fall required must be made by the client and relayed to the installer.	THIS DRAWING MUST NOT BE COPIED OR PASSED TO A THIRD PARTY WITHOUT WRITTEN CONSENT FROM THE MANUFACTURER.	CHECKED	D. P.	TOLERANCE UNLESS OTHERWISE STATED ±5	MATERIAL ALUMINIUM + GLASS					Roofglaze Rooflights Ltd, 11 Howard Road, Eaton Socon, St Neots, Cambs, PE19 8ET Telephone 01480 474797	DRAWING N°. RGR-WO-23-400	REV	ROOFGLAZE
				DATE	12-06-2023										
				DRAWN	R. P.										
				DATE	12-06-2023										
SKYWAY™						DIMENSIONS IN MM	FINISH MARINE GRADE POLYESTER POWDER COAT OPTIONS: RAL 7016 ANTHRACITE GREY, RAL 9005 BLACK, 30% GLOSS					TITLE: SKYWAY FIXED 33mm WALK ON FLATGLASS KERBS BY OTHERS	SIZE A1		Lighting by nature™
								REV	AMENDMENTS	SIGNED	CHECKED	DATE			